

Super Bright 12v Micro-Mini ORION 3250 Series

Specifications:

Description: The Super Bright 12v Micro-Mini ORION series offers high efficiency, low voltage luminaires designed to produce a 120° light beams in cold, frozen and dry environments. This series has endcaps with a 0.63" width and 0.50" height.

Features:

Lighting: Solid state lighting (SSL) LEDs; surface mounted diode (SMD) populated onto printed circuit board (PCB)

Tube and Endcaps: Polycarbonate LEXAN 244R

LEDs: 50mA each

LED Driver Input: 100VAC to 277VAC. Use only UL Listed Class 2 driver

LED Driver Output: 12VDC

Light Beam: 120° viewing angle

Lens : Heat deflection of 300°F

Life: L70 > 50,000 hrs


Operating Temperature Range: -20° C to +85°C

Warranty: 5 year limited warranty from manufacturing defects

Safety Certifications: Luminaires UL/cUL Listed & NSF approved

Certifications: LEDingEDGE Lighting's Quality Management System is ISO 9001:2015 certified

IP Rating: TBD



Options:

Color: Standard CCTs choices are 3000K, 3500K, 4000K, and 5000K with a CRI >90

Endcap: With or without tab

Lens: Clear or frosted

Lengths (rounded to the nearest inch):

Length	# of LEDs	Watts	Length	# of LEDs	Watts	Length	# of LEDs	Watts
4"	4	.625	37	52	8.13	70	100	16.63
7"	8	1.25	40	56	8.75	73	104	16.25
9"	12	1.88	42	60	9.38	75	108	16.88
12"	16	2.5	45	64	10.00	78	112	17.50
15"	20	3.13	48	68	10.63	81	116	18.12
18"	24	3.75	51	72	11.25	84	120	18.75
20"	28	5.00	53	76	11.88	86	124	19.38
23"	32	5.00	56	80	12.50	89	128	20.00
26"	36	5.63	59	84	13.13	92	132	20.63
29"	40	6.25	62	88	13.75	95	136	21.25
31"	44	6.88	64	92	14.38	"Off the Shelf" lengths available at 12", 23", 34" and 45"		
34	48	7.50	67	96	15.00			

Performance Data:

Our custom-built lights have 2,176 variations that affect performance data. Below is the data from one of the many UL tests we have had conducted. Please contact us if you require more specific data for your unique custom-built light fixture.

CCT (K) Nom.	Length (in)	Lens	CRI	CCT (K) Actual	Lumens (lm)	Power (W)	Efficacy (lm/W)
3500	45	Clear	94.1	3513	590.7	4.409	134

Accessories:

Jumpers: Lengths from 3" to 96"; Straight, stripped, right-angle ends; black / white color options

Brackets: Metal, clear Acrylic, Rotating, Magnet



ISO 9001: 2015 Certified

How to create part numbers:

Series	Type	Voltage	Length Options	Color Options (CCT)	Lens Options	Endcap Option
Super Bright, 12v Micro-Mini ORION 3250	Tube	12 volt	12" 23" 34" 45" Etc.	3000K 3500K 4000K 5000K	Clear-C Frosted-F	With tab -add T
MIC3250	T	12V	45	35K	F	T

Example part number: MIC3250-T-12V-45-35K-F-T